

# **PRODUCT DATASHEET**


## **BNC 4 HOLE FLANGE MOUNT SOLDER JACK**

10-371-1-B3



images for illustration purposes only

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LID. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT



					,	
2	CENTRE CONTACT		PHOSPHOR BRONZE		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGNATURE		DATE
		DRAWN	G.E.			25/05/2021
ISSUE	: 1	CHK'D	P.S.			25/05/2021
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D	)			
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

**PTFE** 

**INSULATOR** 

**TW1 4JR** 

#### **Environmental Specification**

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): NONE

#### **Electrical Specification**

Impedance: 50 Ohm Frequency: 1 GHz


Dielectric W/V: 1500 Veff Insulation res: 5000 M-Ohm

#### **Mechanical Specification**

Contact Retention: 10 N min Cable Retention: Not Applicable

Mating cycles: 500 Weight: 9.94 g

### Connector Interface



Tel: +44(0)20 8538 9090 Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com