

PRODUCT DATASHEET


BNC RIGHT ANGLE BULKHEAD LOW PROFILE SHIELDED PCB JACK


10-470-2-B36



images for illustration purposes only

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCITION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT






6	WASHER		SK5		NICKEL	
5	REAR BODY		BRASS		TIN	
4	NUT		BRASS		NICKEL	
3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		PHOSPHOR BRONZE		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
Α4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGN	ATURE	DATE
		DRAWN	I IG			01/05/2014
ISSUE	: 1	CHK'D	GE			01/05/2014

6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. **TW1 4JR**

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS,WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR

Recommended Mounting



Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification

Impedance: 75 Ohm Contact Retention: 10 N min Frequency: 0-2 GHz Cable Retention: N/A Dielectric W/V: 1000 Veff Mating cycles: 250


Insulation res: 5000 M-Ohm Weight: 16.88 g

Connector Interface

image for illustration purposes only



Recommended Panel



Tel: +44(0)20 8538 9090

Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com