


PRODUCT DATASHEET

F TYPE STRAIGHT CRIMP/CRIMP PLUG 15-005-B36-1-FE






5	COUPLING NUT		BRASS		NICKEL	
4	CRIMP SLEEVE		BRASS		NICKEL	
3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		BRASS		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGNATURE		DATE
		DRAWN	G.E.			31/05/17
ISSUE	: 1	CHK'D	I.G.			31/05/17
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

Suitable for Cables:

(FE) Belden 1505F, Bryant BD SD50F

Stripping Dimensions



 $a = 4.0 \, mm$ $b = 8.0 \, \text{mm}$ c = 13.5 mm

 $d = 9.5 \, mm$

* CUT FOIL TO DIM. "b"

Assembly Procedure:

Tooling

Centre Contact: Hex 1.72mm A/F Tool No: 96-HTS-76

Crimp Sleeve: HEX 6.48mm A/F Tool No: 96-HTS-76

Extraction: Not Applicable Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.


IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification

Impedance: 75 Ohm Contact Retention: 10 N min Frequency: 0-3 GHz Cable Retention: 150 N min

Dielectric W/V: 1500 Veff Mating cycles: 250 Insulation res: 5000 M-Ohm Weight: 7.42 g

Connector Interface



THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT