


## 0.4/2.5 MINIATURE RIGHT ANGLE SOLDER / CRIMP JACK 75 Ohm 18-154-D6-AB




images for illustration purposes only



### Suitable for Cables:

(AB) RG179, RG187, Belden 179DT

### Stripping Dimensions



a = 1.0 mm  
b = 5.0 mm  
c = 8.5 mm  
d = 7.5 mm

\* CUT FOIL TO DIM. "b"

### Assembly Procedure: AP017

### Tooling

Centre Contact: Solder

Tool No: Not Applicable

Crimp Sleeve: Hex 3.25mm A/F

Tool No: 336J

### Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP30

### Electrical Specification

Impedance: 75 Ohm

Frequency: 0-3 GHz

Dielectric W/V: 500 Veff

Insulation res: 1000 M-Ohm

### Mechanical Specification

Contact Retention: 5 N min

Cable Retention: 10 N min

Mating cycles: 250

Weight: 1.83 g

### Connector Interface

image for illustration purposes only



6	REAR BODY	BRASS	NICKEL
5	CAP	BRASS	NICKEL
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	PHOS. BRONZE	GOLD
1	FRONT BODY	PHOS. BRONZE	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

<b>A4</b>	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	B00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	IG	13/12/2011
		CHK'D	GE	20/12/2011
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				