


PRODUCT DATASHEET

N TYPE B/H SOLDER / **SOLDER JACK**

25-267-2-B3-HA





RED FIBRE

N/A

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD FARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT

Tel: +44(0)20 8538 9090


)	7	LOCK WASHER		STAINLESS STEEL		PASSIVATED	
	6	NUT		BRASS		NICKEL	
	5	CLAMP NUT		BRASS		NICKEL	
	4	SOLDER SLEEVE		BRASS		GOLD	
	3	INSULATORS		PTFE		N/A	
	2	CENTRE CONTACT		BERYILLIUM COPPER		GOLD	
5	1	BODY		BRASS		NICKEL	
	ITEM	DESCRIPTION		MATERIAL		PLATING	
	Α4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
	REVISION: BOO			NAME	SIGNATURE		DATE
			DRAWN	G.E.			27/11/2020
	ISSUE	: 1	CHK'D	P.S.			27/11/2020
-	6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D	RMATION IS GIVE	N AC AN	INDICATION	I ONI V AND TS
			SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS,WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

FIBRE WASHER

Suitable for Cables:


(HA) RG405 (0.085"), UT85

Stripping Dimensions



a = 5.0 mm

RECOMMENDED MOUNTING:



Environmental Specification

Operating Temp: -65 to +155 Deg C.

IP Rating (Mated): IP 67

Electrical Specification

Impedance: 50 Ohm Frequency: 0-18 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 27 N min Cable Retention: 150 N min

Mating cycles: 500 Weight: 40.10 g

Connector Interface



Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com