




SMA 4 HOLE 17.5mm FLANGE DIRECT SOLDER JACK.

30-279-D3-HA-17.5




images for illustration purposes only



Suitable for Cables:

(HA) RG405 (0.085"), UT85

Stripping Dimensions



a = 2.0 mm
b = 5.5 mm
c = 7.5 mm
d = 5.5 mm

} APPLY FOR
JACKETED
CABLE ONLY

Assembly Procedure: TBC

Tooling

Centre Contact: Solder Tool No: Not Applicable
Crimp Sleeve: Not Applicable Tool No: Not Applicable
Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -65 to +165 Deg C.
IP Rating (Mated): IP 40

Electrical Specification

Impedance: 50 Ohm
Frequency: 0-6 GHz
Dielectric W/V: 750 Veff
Insulation res: 5000 M-Ohm

Mechanical Specification


Contact Retention: 27 N min
Cable Retention: N/A N min
Mating cycles: 500
Weight: 4.66 g

Connector Interface

image for illustration purposes only



Hole Layout



3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BeCu	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	G.E.	07/07/2020
		CHK'D	P.S.	07/07/2020
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				