



MCX STRAIGHT CRIMP/CRIMP PLUG 45-005-D3-AA




images for illustration purposes only



Suitable for Cables:

(AA) RG178, RG196

Stripping Dimensions



a = 5.5 mm
b = 7.0 mm
c = 13.0 mm
d = 7.5 mm

Assembly Procedure: AP020

Tooling

Centre Contact: Indent Crimp Tool No: DMC AFM8 POSITION 5

Crimp Sleeve: Hex 3.25mm A/F Tool No: 336J

Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 40

Electrical Specification

Impedance: 50 Ohm

Frequency: 0-6 GHz

Dielectric W/V: 500 Veff

Insulation res: 1000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min


Cable Retention: 50 N min

Mating cycles: 250

Weight: 1.70 g

Connector Interface

image for illustration purposes only



6	PUSHER SLEEVE	BRASS	NICKEL
5	CRIMP SLEEVE	BRASS	GOLD
4	MALE CONTACT	PHOS. BRONZE	GOLD
3	INSULATORS	PTFE	N/A
2	REAR BODY	BRASS	GOLD
1	FRONT BODY	PHOS. BRONZE	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	G.E.	11/06/2021
		CHK'D	P.S.	11/06/2021
		APP'V'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				