


PRODUCT DATASHEET


1.0/2.3 VERTICAL PCB JACK - TRUE 75 Ohm 52-450-1-D36



images for illustration purposes only


2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT





3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		BeCu		GOLD	
1	BODY		BRASS		GOLD	
ITEM	DESCRIPTION		MATER	IAL PLA		TING
Α4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: BOO			NAME	SIGNATURE		DATE
		DRAWN	G.E.			14/10/19
ISSUE	: 1	CHK'D	P.P.			14/10/19
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

PCB FOOTPRINT:



Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): NONE

Electrical Specification

Impedance: 75 Ohm Frequency: 0-3 GHz

Dielectric W/V: 750 Veff Insulation res: 1000 M-Ohm

Connector Interface



Mechanical Specification

Contact Retention: 10 N min Cable Retention: Not Applicable

Mating cycles: 500 Weight: 1.05 g

Tel: +44(0)20 8538 9090

TW1 4JR

Fax: +44(0)20 8538 9890

Email: info@coax-connectors.com