



MICRO BNC RIGHT ANGLE BULKHEAD PCB JACK

67-468-3-D66



Recommended PCB Layout



Tooling

- Centre Contact: Not Applicable Tool No: Not Applicable
- Crimp Sleeve: Not Applicable Tool No: Not Applicable
- Castellated Nut Spanner: 96-1135 (MAX TORQUE - 115Ncm)

Environmental Specification

- Operating Temp: -55 to +155 Deg C.
- IP Rating (Mated): IP64

Electrical Specification


- Impedance: 75 Ohm
- Frequency: 0-12 GHz
- Dielectric W/V: 1000 Veff
- Insulation res: 5000 M-Ohm

Mechanical Specification

- Contact Retention: 15 N min
- Cable Retention: N/A N min
- Mating cycles: 500
- Weight: 4.77 g


Connector Interface

image for illustration purposes only





- 21.3 dB @ 1.0 GHz
- 31.0 dB @ 3.0 GHz
- 16.8 dB @ 4.5 GHz
- 15.17 dB @ 6.0 GHz


Return Loss Graph



images for illustration purposes only



Recommended Mounting Hole



6	NUT	BRASS	NICKEL
5	INSULATOR	PTFE	N/A
4	CENTRE CONTACT	BeCu	GOLD
3	INSULATOR	PTFE	N/A
2	REAR BODY	BRASS	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	B02	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	BS	31/05/2018
		CHK'D	IG	07/06/2018
		APPV'D		
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR