



## MICRO BNC RIGHT ANGLE BULKHEAD PCB JACK


### 67-468-4-D66




Images for illustration purposes only



### Recommended Mounting Hole



### Recommended PCB Layout



### Tooling

Castellated Nut Spanner: 96-1135 (MAX TORQUE - 115Ncm.)

### Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

### Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12.0 GHz

Dielectric W/V: 1000 Veff

Insulation res: 5000 M-Ohm

### Mechanical Specification

Contact Retention: 15 N min


Cable Retention: N/A

Mating cycles: 500

Weight: 4.14 g

### Connector Interface


Image for illustration purposes only



### Performance

- 21.35dB @ 1.0 GHz
- 31.07dB @ 3.0 GHz
- 16.79dB @ 4.5 GHz
- 15.17dB @ 6.0 GHz

### Return Loss Graph



5	NUT	BRASS	NICKEL
4	REAR BODY	BRASS	GOLD
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

<b>A4</b>	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	PP	28/06/2019
		CHK'D	I.G.	04/07/2019
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				