



TNC RIGHT ANGLE SOLDER / CRIMP PLUG 13-105-B3-DC




images for illustration purposes only



Suitable for Cables:

(DC) LMR300

Stripping Dimensions



a = 4.0 mm
b = 10.0 mm
c = 23.0 mm
d = 19.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP017

Tooling

Centre Contact: SOLDER Tool No: N/A

Crimp Sleeve: Hex 8.23mm A/F Tool No: 336D

Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C

IP Rating (Mated): NONE

Electrical Specification

Impedance: 50 Ohm

Frequency: 0 -3 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min


Cable Retention: 220N min

Mating cycles: 500

Weight: 30.24 g

Connector Interface

image for illustration purposes only



7	RETAINING WASHER	BRASS	NICKEL
6	REAR BODY	BRASS	NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BRASS	GOLD
1	FRONT BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	G.E.	19/10/2020
		CHK'D	P.S.	19/10/2020
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				