


TNC BULKHEAD CRIMP/CRIMP JACK

13-264-B3-AA




images for illustration purposes only



Suitable for Cables:

(AA) RG178, RG196

Stripping Dimensions



a = 3 mm
b = 6 mm
c = 12 mm
d = 9 mm

Assembly Procedure: AP011

Tooling

Centre Contact: Indent Crimp Tool No: DMC AFM8 Posn. 7

Crimp Sleeve: Hex 3.25mm A/F Tool No: 336J

Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -30 to +70 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 50 Ohm

Frequency: 0-4.0 GHz

Dielectric W/V: 750 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min

Cable Retention: 50 N min

Mating cycles: 500

Weight: 17.09 g

Connector Interface

image for illustration purposes only



9	SPACER	PTFE	N/A
8	MALE CONTACT	BRASS	GOLD
7	WASHERS	SK5	NICKEL
6	PUSHER SLEEVE	BRASS	NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	DELIN	N/A
2	FEMALE CONTACT	PHOS. BRONZE	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	G.E.	11/06/2021
		CHK'D	P.S.	11/06/2021
		APP'V'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				