



## HD43 STRAIGHT CRIMP/CRIMP SOCKET 7FS

### 43-061-D6-BF




images for illustration purposes only



### Suitable for Cables:

(BF) RA7000, BT7000

### Stripping Dimensions



a = 4.5 mm  
b = 8.0 mm  
c = 21.0 mm  
d = 16.5 mm

\* CUT FOIL TO DIM. "b"

### Assembly Procedure: AP023

### Tooling

Centre Contact: Square Crimp Tool No: HTS-43

Crimp Sleeve: HEX 5.18mm A/F Tool No: HTS-43

Alignment Tool: Not Applicable Extraction: Not Applicable

### Environmental Specification

Operating Temp: -40 to +100 Deg C

IP Rating (Mated): NONE

### Electrical Specification

Impedance: 75 Ohm

Frequency: 0 - 3 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

### Mechanical Specification

Contact Retention: 22 N min


Cable Retention: 220 N min

Mating cycles: 250

Weight: 5.22 g

### Connector Interface

image for illustration purposes only



7	SLEEVE / SPRING	NYLON	N/A
6	OUTER CONTACT	PHOSPHOR BRONZE	GOLD
5	LATCHING SLEEVE	BRASS	NICKEL
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

<b>A4</b>	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A04		NAME	SIGNATURE	DATE
DRAWN	GE				04/04/2007
ISSUE :	2		CHK'D	IG	17/12/2007
<b>6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR</b>		APPV'D			
<small>THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.</small>					