



BNC INSULATED BULKHEAD JACK TO JACK ADAPTOR 4.5GHz 10-503-B36



images for illustration purposes only



Suitable for Cables:

N/A

Environmental Specification

Operating Temp: -35 to +70 Deg C

IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification

Impedance: 75 Ohm

Contact Retention: 10 N min

Frequency: 0 - 4.5 GHz

Cable Retention: N/A


Dielectric W/V: 1500 Veff

Mating cycles: 500

Insulation res: 5000 M-Ohm

Weight: 14.34 g


Recommended Mounting Hole



5.0 MAX PANEL THICKNESS

Connector Interface

image for illustration purposes only



Performance


-29.4 dB @ 1.0 GHz

-42.8 dB @ 2.0 GHz

-27.9 dB @ 4.5 GHz

-20.5 dB @ 6.0 GHz

Return Loss Graph



6	WASHER	BeCu	NICKEL
5	NUT	BRASS	NICKEL
4	INSULATION	ABS	N/A
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	PHOS. BRONZE	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A02	NAME	SIGNATURE	DATE
ISSUE :	2	DRAWN	IG	02/04/2013
		CHK'D	GE	04/04/2013
		APP'V'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				