




TNC STRAIGHT BULKHEAD JACK TO JACK ADAPTOR 13-501-A3



images for illustration purposes only



Tooling

Centre Contact: Not Applicable Tool No: Not Applicable

Crimp Sleeve: Not Applicable Tool No: Not Applicable

Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP64

Electrical Specification Mechanical Specification

Impedance: 50 Ohm

Contact Retention: 10 N min

Frequency: 0-3 GHz

Cable Retention: N/A

Dielectric W/V: 1500 Veff

Mating cycles: 250


Insulation res: 5000 M-Ohm Weight: 19.37 g

Connector Interface

Mounting Hole Details



image for illustration purposes only



4.0 MAX PANEL THICKNESS

Performance


-21.17dB @ 1.0 GHz

-20.7dB @ 2.0 GHz

-18.79dB @ 3.0 GHz

-13.3dB @ 4.5 GHz

Return Loss Graph



6	WASHER	Fe	NICKEL
5	RETAINER	BRASS	NICKEL
4	NUT	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	PHOSPHOR BRONZE	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A00	NAME	SIGNATURE	DATE
ISSUE :	0	DRAWN	IG	03/03/2014
		CHK'D	GE	04/03/2014
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR				
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				