


PRODUCT DATASHEET

BNC STRAIGHT SOLDER/CLAMP JACK 10-050-A3-AH



THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT




GENERAL TOLERANCE = ±0.2mm

7	WASHERS		BRASS		NICKEL	
6	NUT		BRASS		NICKEL	
5	GASKET		SILICONE		N/A	
4	CLAMP		BRASS		NICKEL	
3	INSULATOR		DELRIN		N/A	
2	CENTRE CONTACT		BRASS		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: BOO			NAME	SIGNATURE		DATE
		DRAWN	G.E.			16/10/2023
ISSUE	: 1	CHK'D	P.S.			16/10/2023
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.				

Suitable for Cables:

(AH) RG58, RG141, LMR195, URM43, URM76, WBC195, PSF 1/6, KX15, KX23

Stripping Dimensions



 $a = 3.0 \, \text{mm}$ $b = 4.5 \, \text{mm}$ c = 5.5 mm

d = 2.5 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure:

Tooling

Centre Contact: Solder Tool No: Solder

Crimp Sleeve: Not Applicable Tool No: Not Applicable

Extraction: Not Applicable Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -30 to +70 Deg C.

IP Rating (Mated): IP 40

Electrical Specification Mechanical Specification

Impedance: 50 Ohm Contact Retention: 10 N min Frequency: 0-1 GHz Cable Retention: 150 N min

Dielectric W/V: 1500 Veff Mating cycles: 500 Insulation res: 5000 M-Ohm Weight: 13.05 g

Connector Interface

