



BNC RIGHT ANGLE CRIMP / CRIMP PLUG 10-104-B126-EF1




images for illustration purposes only



Suitable for Cables:

(EF) Belden 1855A

Stripping Dimensions



a = 4.0 (0.1575")
b = 8.0 (0.3150")
c = 16.0 (0.6299")
d = 12.0 (0.4724")

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP019

Tooling

Centre Contact: **SQ 1.07mm (0.0421") A/F** Tool No: 96-HTS-77

Crimp Sleeve: **Hex 4.52mm(0.178") A/F** Tool No: 96-HTS-77

Alignment Tool: **Not Applicable** Extraction: 96-2208

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 15 N min


Cable Retention: 100 N min

Mating cycles: 500

Weight: 25.15 g

Connector Interface

image for illustration purposes only



Performance


-22.25 dB @ 3.0 GHz

-18.25 dB @ 6.0 GHz

-18.95 dB @ 9.0 GHz

-19.17 dB @ 12.0 GHz

Return Loss Graph



8	MALE CONTACT	BRASS	GOLD
7	WASHERS	SK5	NICKEL
6	COUPLING NUT	ZINC	NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	NICKEL

ITEM	DESCRIPTION	MATERIAL	PLATING
A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES	
REVISION :	A01	NAME	SIGNATURE
ISSUE :	1	DATE	
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		DRAWN	G.E.
		CHK'D	P.S.
		APPV'D	
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.			