


BNC RIGHT ANGLE CRIMP / CRIMP PLUG 10-104-W126-BS




images for illustration purposes only



Suitable for Cables:

(BS) KLOTZ VDU042LP

Stripping Dimensions



a = 4.0

b = 8.0

c = 16.0

d = 12.0

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP019

Tooling

Centre Contact: SQ 0.95mm A/F

Tool No: HTS-43

Crimp Sleeve: Hex 4.52mm A/F

Tool No: HTS-43

Alignment Tool: Not Applicable

Extraction: 96-2208

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 15 N min


Cable Retention: 100 N min

Mating cycles: 500

Weight: 26.64 g

Connector Interface

image for illustration purposes only



8	MALE CONTACT	BRASS	GOLD
7	WASHERS	SK5	NICKEL
6	COUPLING NUT	BRASS	BLACK NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4

SHEET 1 OF 1

DIMENSIONS ARE IN MILLIMETRES

REVISION : A01

NAME	SIGNATURE	DATE
DRAWN	G.E.	12/05/2022
CHK'D	P.S.	12/05/2022
APPV'D		

ISSUE : 1

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.