


BNC STRAIGHT PLUG TO PLUG ADAPTOR 10-514-A3



images for illustration purposes only



Environmental Specification

Operating Temp: -30 to +70 Deg C.

IP Rating (Mated): IP 54

Electrical Specification

Impedance: 50 Ohm

Frequency: 0-3 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min


Cable Retention: Not Applicable

Mating cycles: 250

Weight: 15.25 g

Connector Interface (Both Ends)

image for illustration purposes only



8	RETAINING RING	SK5	NICKEL
7	SPRINGS	SK5	NICKEL
6	COUPLING NUT	ZINC	NICKEL
5	GASKET	SILICONE	N/A
4	WASHERS	BRASS	NICKEL
3	INSULATOR	POM	N/A
2	CENTRE CONTACT	BRASS	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

A4

SHEET 1 OF 1

DIMENSIONS ARE IN MILLIMETRES

REVISION : A00

ISSUE : 1

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

NAME	SIGNATURE	DATE
DRAWN G.E.		23/10/2025
CHK'D P.S.		23/10/2025
APPV'D		

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.