

PRODUCT DATASHEET

TNC STRAIGHT FRONT MOUNT BULKHEAD SOLDER BUCKET JACK


13-388-2-B3-RD



images for illustration purposes only

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCITION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT





4	RETAINER		BRASS		NICKEL	
3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		BERYLLIUM COPPER		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGNATURE		DATE
ISSUE: 1		DRAWN	G.E.			11/07/2023
		CHK'D	P.S.			11/07/2023
	•	A DDV/ID				

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

APPV'D

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR

Tooling

Centre Contact: Solder Tool No: Solder

Crimp Sleeve: Not Applicable Tool No: Not Applicable

Alignment Tool: Not Applicable Extraction: Not Applicable

Weight: 6.01 g

Environmental Specification

Operating Temp: -65 to +165 Deg C.

IP Rating (Mated): IP 40

Electrical Specification Mechanical Specification

Impedance: 50 Ohm Contact Retention: 10 N min
Frequency: 0-11 GHz Cable Retention: Not Applicable
Dielectric W/V: 1500 Veff Mating cycles: 500

Connector Interface

Insulation res: 5000 M-Ohm



TW1 4JR TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.

Tel: +44(0)20 8538 9090 Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com