



PRODUCT DATASHEET

BNC VERTICAL PCB MOUNT JACK 10-452-B6-28




images for illustration purposes only





3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		PHOSPHOR BRONZE		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATER	IAL	PLATING	
Α4	SHEET 1 OF 1	/	DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00		ROHS 2002/95/EC	NAME	SIGN	ATURE	DATE
		DRAW	G.E.			06/05/2022
ISSUE	: 2	CHK'D	P.S.			06/05/2022
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

Recommended PCB Layout



Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): NONE

Impedance: 75 Ohm Frequency: 0-1 GHz


Dielectric W/V: 1500 Veff Insulation res: 5000 M-Ohm

Electrical Specification Mechanical Specification

Contact Retention: 10 N min Cable Retention: Not Applicable

Mating cycles: 500 Weight: 8.56 g

Connector Interface



Fax: +44(0)20 8538 9890

Tel: +44(0)20 8538 9090

TW1 4JR

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT

Email: info@coax-connectors.com