


PRODUCT DATASHEET

BNC STRAIGHT CRIMP/CRIMP PLUG 10-005-W126-FC2






	7	WASHERS		SK5		NICKEL	
ELD. NEI NODO	6	COUPLING NUT		BRASS		BLACK NICKEL	
	5	GASKET		SILICONE		N/A	
OI AI AFOI ONS	4	CRIMP SLEEVE		BRASS PTFE		NICKEL N/A	
	3	INSULATOR					
	2	CENTRE CONTAC	СТ	BRASS		GOLD	
5	1	BODY		BRASS		GOLD	
	ITEM	DESCRIPTION		MATERIAL		PLATING	
	A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			METRES
2	REVISION: BOO		ROHS 2002/95/EC	NAME	SIGNATURE		DATE
			DRAWN	G.E.			23/05/2025
	ISSUE	: 1	CHK'D	P.S.			23/05/2025
2	6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
2 2013. IIIIS DOCOMENTIS IIIET NOI ENT			THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR MODIFICATIONS NECESSARY WITHOUT PRIOR MODIFICE.				

Suitable for Cables:

(FC2) BD SD10F

Stripping Dimensions



 $a = 4.0 \, mm$ $b = 8.0 \, mm$ c = 16.0 mm

d = 12.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: Hex 1.72mm A/F Tool No: 96-HTS-75A

Crimp Sleeve: Hex 8.23mm A/F Tool No: 96-HTS-75A

Extraction: 96-2208 Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification Contact Retention: 10 N min

Impedance: 75 Ohm Frequency: 0-18 GHz


Dielectric W/V: 1500 Veff

Cable Retention: 200 N min Mating cycles: 500

Insulation res: 5000 M-Ohm

Weight: 12.05 g

Connector Interface



Tel: +44(0)20 8538 9090

THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT

Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com