



2.92 (K) EASYFIT / SOLDER - CLAMP PLUG 30K-041-HP3-HA




images for illustration purposes only



Suitable for Cables:

(HA) RG405 (0.085"), UT85

Stripping Dimensions



a = 2.0 mm

Assembly Procedure: Not Applicable

Tooling

Centre Contact: Not Applicable Tool No: Not Applicable

Crimp Sleeve: Solder Tool No: Solder

Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 54

Electrical Specification

Impedance: 50 Ohm

Frequency: 0- 40 GHz

Dielectric W/V: 1000 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 27 N min


Cable Retention: 100 N min

Mating cycles: 250

Weight: 6.38 g

Connector Interface

image for illustration purposes only



7	RETAINING WASHER	STAINLESS STEEL	PASSIVATED
6	NUT	STAINLESS STEEL	PASSIVATED
5	GASKET	SILICONE	N/A
4	SOLDER FERRULE	BRASS	GOLD
3	INSULATOR	PPO	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	STAINLESS STEEL	PASSIVATED
ITEM	DESCRIPTION	MATERIAL	PLATING

A4

SHEET 1 OF 1

DIMENSIONS ARE IN MILLIMETRES

REVISION : A02

ISSUE : 1

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

NAME	SIGNATURE	DATE
DRAWN G.E.		25/06/2025
CHK'D P.S.		25/06/2025
APPV'D		

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.