



## BNC STRAIGHT CRIMP/CRIMP PLUG 10-005-B126-JB




images for illustration purposes only



### Suitable for Cables:

(JB) Percon VK60S+

### Stripping Dimensions



a = 4.0 mm  
b = 8.0 mm  
c = 16.0 mm  
d = 12.0 mm

\* CUT FOIL TO DIM. "b"

### Assembly Procedure: AP001

### Tooling

Centre Contact: Hex 1.72mm A/F Tool No: 96-HTS-76

Crimp Sleeve: HEX 6.48mm A/F Tool No: 96-HTS-76

Alignment Tool: Not Applicable Extraction: 96-2208

### Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 50

### Electrical Specification

Impedance: 75 Ohm

Frequency: 0-18 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Surpasses ST2081-1 & ST2082-1 for 6G-SDI & 12G-SDI

### Mechanical Specification

Contact Retention: 10 N min


Cable Retention: 200 N min

Mating cycles: 500


Weight: 9.92 g

### Connector Interface

image for illustration purposes only



7	WASHERS	SK5	NICKEL
6	COUPLING NUT	ZINC	NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BRASS	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING

<b>A4</b>	<b>SHEET 1 OF 1</b>		<b>DIMENSIONS ARE IN MILLIMETRES</b>		
<b>REVISION :</b>	<b>A00</b>	<b>DRAWN</b>	G.E.		21/08/2025
<b>ISSUE :</b>	<b>1</b>	<b>CHK'D</b>	P.S.		21/08/2025
<b>6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR</b>		<b>APPV'D</b>			
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.					