



HD43 STRAIGHT CRIMP/CRIMP PLUG 5GTIS

43-012-1-D6-BD




images for illustration purposes only



Suitable for Cables:

(BD) BT3002, TZC75024, TZC75025

Stripping Dimensions



a = 4.5 mm
b = 8.0 mm
c = 21.0 mm
d = 16.5 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP023

Tooling

Centre Contact: Square Crimp Tool No: HTS-43

Crimp Sleeve: HEX 4.52mm A/F Tool No: HTS-43

Alignment Tool: Not Applicable Extraction: 96-832-TOOL

Environmental Specification

Operating Temp: -40 to +100 Deg C

IP Rating (Mated): NONE

Electrical Specification

Impedance: 75 Ohm

Frequency: 0 - 3 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 22 N min


Cable Retention: 150 N min

Mating cycles: 250

Weight: 3.95 g

Connector Interface

image for illustration purposes only



5	RETAINING CLIP	PA 46	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	PHOSPHOR BRONZE	GOLD
1	BODY	BRASS	NICKEL/GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	ROHS 2002/95/EC		DIMENSIONS ARE IN MILLIMETRES	
REVISION : A00		DRAWN	G.E.		09/10/2025
ISSUE : 1		CHK'D	P.S.		09/10/2025
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D			
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.					