



1.0/2.3 STRAIGHT CRIMP/CRIMP JACK

52-054-D6-BH




images for illustration purposes only



Suitable for Cables:

(BH) Belden 735A, CT1320

Stripping Dimensions



a = 3.5 mm
b = 8.0 mm
c = 12.0 mm
d = 15.5 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: 0.95mm A/F

Tool No: 96-HTS-43

Crimp Sleeve: Hex 4.52mm A/F

Tool No: 96-HTS-43

Alignment Tool: 100-1023

Extraction: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 40

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-3 GHz

Dielectric W/V: 750 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min


Cable Retention: 110 N min

Mating cycles: 500

Weight: 3.28 g

Connector Interface

image for illustration purposes only



6	REAR BODY	BRASS	NICKEL
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4

SHEET 1 OF 1

DIMENSIONS ARE IN MILLIMETRES

REVISION : A00

NAME SIGNATURE DATE

ISSUE : 1

DRAWN G.E. 21/10/2025
CHK'D P.S. 21/10/2025

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS
SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL
GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT
TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR
NOTICE.